





未注公差/General tolerances(mm)

0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

0.1/10
±2°

REV	ECN	DESCRIPTION	DRFT	DATE



PCB Layout

DB124 — 3.81 — XXP — C — S/P
(Series No.) (Pitch) (Poles) Slotted/Phillips
(Color):GN:(Green), BK:(Black), BU:(Blue), RD:(Red), GY:(Gray)
OG:(Orange), WT:(White), YL:(Yellow), CR:(Clear)

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/10	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/ 污染等级/Pollution Degree	III/3	III/2	II/3
额定电压/电流/Rated Voltage(V)/Current(A)	160/10	250/10	400/10
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	2.5	2.5	2.5
螺丝扭矩/Torque Tightening(N·m/Lb.in)	M2.0 0.2N.m/2.0Lb.in		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	1.0/26-16		
间距/Pitch(mm)/线数范围/Poles	3.81/(02-24)		
剥线长度/Stripping length(mm)	/		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

4	Screw	Steel	M2/Zn plated
3	Cage	Copper alloy	M2/Ni plated
2	Housing	PA66	UL94V-0
1	Pin header	Copper alloy	Sn plated
ITEM	NAME OF PART	MATERIAL	NOTES

MAT NO.:	/	DORABO 宁波地博电气有限公司 NINGBO DORABO ELECTRICAL CO., LTD		
STATUS:	/	NAME: DB124-3.81-XXP-C-S		
APPD: J.Ting Chen	2025.07.14	DRAWING NO.:		
CHKD: Duck Mao	2025.07.14	REV M1		
DRFT: Steven Lu	2025.07.14	TYPE: CUSTOMER_DRAWING		
SIZE: A4	mm (inch)	SCALE: 1:1 SHEET 1/1		