



# CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO.: CQC21003311454

Valid from: Sep.03,2021

Valid until:long-term

**NAME AND REGISTERED ADDRESS OF THE APPLICANT** CIXI DORABO ELECTRONICS.,LTD  
NO.828 CANGDA ROAD,CHANGHE TOWN,CIXI CITY,ZHEJIANG PROVINCE

**NAME AND REGISTERED ADDRESS OF THE MANUFACTURER** CIXI DORABO ELECTRONICS.,LTD  
NO.828 CANGDA ROAD,CHANGHE TOWN,CIXI CITY,ZHEJIANG PROVINCE

**NAME AND LOCATION OF THE FACTORY** CIXI DORABO ELECTRONICS.,LTD  
NO.828 CANGDA ROAD,CHANGHE TOWN,CIXI CITY,ZHEJIANG PROVINCE

**PRODUCT NAME, MODEL AND SPECIFICATION** Connecting device with screw-type clamping units  
See appendix

**THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS** GB/T 13140.1-2008;GB/T 13140.2-2008

**TYPE OF CERTIFICATION SCHEMES** Type Testing of Product + Initial Factory Inspection + Follow up Factory Inspection

This is to certify that the above mentioned product(s) complies with the requirements of certification rules of CQC11-462195-2011.  
The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body.

The certificate information is available through the QR code below or CNCA's website: [www.cnca.gov.cn](http://www.cnca.gov.cn)



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



# CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO. : CQC21003311454

page 1 of 2

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	名称	电压 (V)	额定连接容 量(mm <sup>2</sup> )	最高使用 环境温度
1	DB300V-b-XXP 其中, XX=2~12, 为产品的位数; b=5.0/7.5, 代表导电件之间的间距: 5.0mm/7.5mm;	300	0.5~2.5	T120
2	DB166-5.0-XXP 其中, XX=2~12, 为产品的位数; 5.0代表导电件之间的间距: 5.0mm	300	0.5~2.5	T120
3	DB167-5.0-XXP 其中, XX=2~12, 为产品的位数; 5.0代表导电件之间的间距: 5.0mm	300	0.5~2.5	T120
4	DB126a-5.0-XXP 其中, XX=2~12, 为产品的位数; a=V/R, 代表产品的导电件角度: 直针/弯针; 5.0代表导电件之间的间距: 5.0mm	250	0.5~2.5	T120
5	DB126a-7.5-XXP 其中, XX=2~12, 为产品的位数; a=V/R, 代表导电件角度: 直针/弯针; 7.5代表导电件之间的间距: 7.5mm	300		T120
6	DB301a-b-XXP 其中, XX=2~12, 为产品的位数; a=V/R, 代表导电件角度: 直针/弯针; b=3.5/3.81, 代表导电件之间的间距: 3.5mm/3.81mm;	250	0.5~1.0	T120
7	DB301a-5.0-XXP 其中, XX=2~12, 为产品的位数; a=V/R, 代表导电件角度: 直针/弯针; 5.0代表导电件之间的间距: 5.0mm	300	0.5~1.5	T120



CHINA QUALITY CERTIFICATION CENTRE




# CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO. : CQC21003311454

page 2 of 2

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.



**CHINA QUALITY CERTIFICATION CENTRE**