

REVISION RECORD

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------

NOTES1:

UL Standard

- 1.Rated Voltage/Current : 300V / 30A
- 2.Torque Value : M3 , 4.43Lb.in
- 3.Wire Range : 18~10AWG

IEC Standard

- 1.Rated Voltage/Current : 450V / 41A
- 2.Torque Value : M3 , 0.5N·m
- 3.Wire Range : 1.0~6.0mm²

NOTES2:

- 1.Dimension shall be interpreted per ASME Y14.5-2009
- 2.Pitch : 10.00mm, Poles : N=02~12P
- 3.Stripping length : 8mm
- 4.Withstanding Voltage : AC2000V/1Min.
- 5.Operating temperature: -40°C~+105°C
- 6.Undimensioned Tolerances:

Pitch range in mm		Nominal dimension range in mm						0.1/10
TO 6	Over 6 TO 10	Over 10 TO 24	TO 30	Over 30 TO 60	Over 60 TO 100	Over 100 TO 150	Over 150	≤
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2°

7.RoHS Compliance

DB10H-10.0 - XXP - 1Y - 100A (H)
(Series No.) (Poles) (Single Pitch) (Color): 1.(Grey)
2.(Blue)
3.(Black)
4.(Green)
5.(Orange)
6.(Red)
7.(Transparent)
8.(Yellow)
9.(White)

DETACHED LISTS	PART NO.:	/				DORABO 慈溪市地博电子有限公司 CIXI DORABO ELECTRONICS CO.,LTD	
	APPD:	/		NAME:			DB10H-10.0-XXP-1Y-00A(H)
	CHKD:	/		TITLE:			CUSTOMER DRAWING
	DRFT:	/		DRAWING NO.:		REV	DO
	THIRD ANGLE PROJECTION		MM (INCH)		DO NOT SCALE DRAWING		SCALE 1:1