




未注公差/General tolerances(mm)

0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

0.1/10
±2°

REV	ECN	DESCRIPTION	DRFT	DATE

PCB LAYOUT

7.62*(XX-1)

DB2EB — 7.62 — XXP — C — XXXX

(Series No.) (Pitch) (Poles) (Customer Request)

(Color):GN:(Green), BK:(Black), BU:(Blue), RD:(Red), GY:(Gray)
OG:(Orange), WT:(White), YL:(Yellow), CR:(Clear)

2P: Clasp on the left
from this view

DORABO
DB2EB-7.62

UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准/IEC Standard:	III/3	III/2	II/2
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电压/Rated Voltage(V)/Current(A)	500/20	630/20	1000/20
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6	6	6
间距/Pitch(mm)/线数范围/Poles	7.62/XX=2~16P		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MAT NO.: /	DORABO 宁波地博电气有限公司 NINGBO DORABO ELECTRICAL CO., LTD			
STATUS: /				
APPD: Steven Lu 2025.12.7	NAME: DB2EB-7.62-XXP-C			
CHKD: Jting Chen 2025.12.7				
DRFT: Tom Mao 2025.12.7	DRAWING NO.: /		REV	TO
SIZE: A4	mm (inch)	TYPE: CUSTOMER DRAWING	SCALE:	SHEET 1/1